

# **D** Wood Windows












































- Grill options include 1LT, GBG, or SDL. SDL may be 7/8" or 1 1/4", PVC or wood.
- Cardinal Insulated double pane glass, available clear IG or Low-E. Some sizes may be tempered.
- Non-rot Marley PVC sill standard
- Truth sash lock standard
- Primed brickmould standard. PVC brickmould & 1x4bb available
- Primed blindstop standard, PVC blindstop available

- Exterior wood primed and ready to accept paint.
- Interior natural wood can be painted or stained
- Foam filled weather-stripping between top and bottom sash
- Compression balance provides tilting of sash for hassle-free cleaning of exterior glass
- Entire length of bottom sash rail routed with finger lift for easy operation

Dyke Industries, Inc.  
www.dykeatlanta.com  
(770) 441-9811

April 2008

# Stock Window Sizes

Masonry Opening		Double Hung						Picture		
		2 <sup>0</sup>	2 <sup>4</sup>	2 <sup>8</sup>	3 <sup>0</sup>	3 <sup>4</sup>	3 <sup>8</sup>	3 <sup>4</sup>	4 <sup>4</sup>	5 <sup>4</sup>
Rough Opening		1 <sup>10</sup>	2 <sup>2</sup>	2 <sup>6</sup>	2 <sup>10</sup>	3 <sup>2</sup>	3 <sup>6</sup>	3 <sup>2</sup>	4 <sup>2</sup>	5 <sup>2</sup>
3 <sup>6</sup> ¼	3 <sup>5</sup> ½	 1 <sup>8</sup> x 3 <sup>2</sup>	 2 <sup>0</sup> x 3 <sup>2</sup>	 2 <sup>4</sup> x 3 <sup>2</sup>	 2 <sup>8</sup> x 3 <sup>2</sup>	 3 <sup>0</sup> x 3 <sup>2</sup>				
4 <sup>2</sup> ¼	4 <sup>1</sup> ½		 2 <sup>0</sup> x 3 <sup>10</sup>	 2 <sup>4</sup> x 3 <sup>10</sup>	 2 <sup>8</sup> x 3 <sup>10</sup>	 3 <sup>0</sup> x 3 <sup>10</sup>		 3 <sup>0</sup> x 3 <sup>10</sup>	 4 <sup>0</sup> x 3 <sup>10</sup>	
4 <sup>10</sup> ¼	4 <sup>9</sup> ½	 1 <sup>8</sup> x 4 <sup>6</sup>	 2 <sup>0</sup> x 4 <sup>6</sup>	 2 <sup>4</sup> x 4 <sup>6</sup>	 2 <sup>8</sup> x 4 <sup>6</sup>	 3 <sup>0</sup> x 4 <sup>6</sup>	 3 <sup>4</sup> x 4 <sup>6</sup>		 4 <sup>0</sup> x 4 <sup>6</sup>	 5 <sup>0</sup> x 4 <sup>6</sup>
5 <sup>6</sup> ¼	5 <sup>5</sup> ½	 1 <sup>8</sup> x 5 <sup>2</sup>	 2 <sup>0</sup> x 5 <sup>2</sup>	 2 <sup>4</sup> x 5 <sup>2</sup>	 2 <sup>8</sup> x 5 <sup>2</sup>	 3 <sup>0</sup> x 5 <sup>2</sup>	 3 <sup>4</sup> x 5 <sup>2</sup>	 3 <sup>0</sup> x 5 <sup>2</sup>	 4 <sup>0</sup> x 5 <sup>2</sup>	 5 <sup>0</sup> x 5 <sup>2</sup>
5 <sup>10</sup> ¼	5 <sup>9</sup> ½		 2 <sup>0</sup> x 5 <sup>6</sup>	 2 <sup>4</sup> x 5 <sup>6</sup>	 2 <sup>8</sup> x 5 <sup>6</sup>	 3 <sup>0</sup> x 5 <sup>6</sup>				
6 <sup>6</sup> ¼	6 <sup>5</sup> ½	 1 <sup>8</sup> x 6 <sup>2</sup>	 2 <sup>0</sup> x 6 <sup>2</sup>	 2 <sup>4</sup> x 6 <sup>2</sup>	 2 <sup>8</sup> x 6 <sup>2</sup>	 3 <sup>0</sup> x 6 <sup>2</sup>	 3 <sup>4</sup> x 6 <sup>2</sup>	 3 <sup>0</sup> x 6 <sup>2</sup>	 4 <sup>0</sup> x 6 <sup>2</sup>	 5 <sup>0</sup> x 6 <sup>2</sup>



Double Hung Sash (boot glazed)  
Wood frame, double glazed  
Low E coating (e=0.042, s2)

## Energy Performance Ratings

U-Factor (U.S./I-P)

**0.38**

Solar Heat Gain coefficient

**0.31**

## Additional Performance Ratings

Visible Transmittance

**.52**

Condensation Resistance

**52**

